



F2 105



25



Kubota V1505



Ø 25, 30, 35, 40, 45,
50, 55, 60, 65, 70,
80, 90, 100 cm



- Lung.: 241 cm
- Larg.: allarg. idr. da 84 cm a 112 cm
- Alt.: 226 cm

- Kubota V1505, 3 cilindri
- 25 CV a 3000 giri/min

0 - 3 km/h
0 - 6 km/h

1950 kg

23 cm



- Length: 94.88 in
- Width: hydr. adj. 33.07 in to 44.09 in
- Height: 88.98 in

- Kubota V1505, 3 cylinders
- 25 HP at 3000 RPM

0 - 1,86 mph
0 - 3,73 mph

4299,01 lb

9,06 in



- Long.: 241 cm
- Larg.: élarg. hydr. de 84 cm à 112 cm
- Haut.: 226 cm

- Kubota V1505, 3-cylindres
- 25 CV a 3000 TR/min

0 - 3 km/h
0 - 6 km/h

1950 kg

23 cm



- Long.: 241 cm
- Anch.: enhanche hydr. de 84 cm a 112 cm
- Alt.: 226 cm

- Kubota V1505, 3-cilindros
- 25 CV a 3000 RPM

0 - 3 km/h
0 - 6 km/h

1950 kg

23 cm



- Länge: 241 cm
- Breite: hydraulisch einstellbare Breite von 84 cm bis 112 cm
- Höhe: 226 cm

- Kubota V1505, 3Zylindern
- 25 PS bei 3000 u/MIN

0 - 3 km/h
0 - 6 km/h

1950 kg

23 cm



Via N. Rodolico, 31 - 51100 Pistoia (PT) - ITALY
Tel.: +39 0573/528456 - Fax: +39 0573/520956

P. IVA: IT01103500474

www.pazzaglia.it - info@pazzaglia.it